



FLOATING PLATFORM · WORK BARGE SERIES

# Floating platform, *Work Barge series.*

Five standard Work Barge models from 12 m × 6 m to 16 m × 8 m, with deadweight from 6 to 30 tonnes. FRP grating deck on hot-dip galvanised steel floaters and HDPE pipe superstructure. Hydraulic crane up to 20 MT, polyurea coating optional. Engineered for fish farm feeding, cage installation and maintenance operations.

17

YEARS · SINCE  
2009

39

EXPORT COUNTRIES

5

WORK BARGE MODELS

30 t

MAX DEADWEIGHT

Engineered. Manufactured. *Deployed.*[ASAKUA.COM](https://www.asakua.com)


**CAGE FEEDING PLATFORM**

**FRP DECK · GALVANISED FLOATERS**

**ON-SITE OPERATIONS**
**WORK BARGE SERIES · MODULAR CONSTRUCTION**

# Steel floaters, FRP deck, HDPE superstructure.

Hot-dip galvanised steel floaters carry an **FRP grating deck** and a polyethylene pipe superstructure. Five standard models from 6 to 30 tonnes deadweight; deck cargo capacity 1–4 t/m<sup>2</sup>. Hydraulic crane up to 20 MT, manual crane up to 12 T optional. **Polyurea coating** on the steel structure is available for additional corrosion protection. Engineering, fabrication, pre-assembly, transport and on-site installation are delivered turnkey.

MODEL	SIZE	DEADWEIGHT	DECK LOAD	CRANE (MAX)
P1260L	12 × 6 m	6 t	1 t/m <sup>2</sup>	manual 3 T
P1680L	16 × 8 m	12 t	2 t/m <sup>2</sup>	manual 6 T
P1260H	12 × 6 m	16 t	3 t/m <sup>2</sup>	8 MT
P1680H	16 × 8 m	24 t	4 t/m <sup>2</sup>	16 MT
P1680S	16 × 8 m	30 t	4 t/m <sup>2</sup>	20 MT

**FIVE STANDARD MODELS · CUSTOM BUILDS**

P1260L (entry, 6 t cargo) to P1680S (flagship, 30 t cargo + 20 MT crane). Beyond the standard range, custom-sized platforms are produced for project-specific deck areas, equipment and load. ASAKUA delivers turnkey: engineering, steel fabrication, pre-assembly, transport, on-site installation.

**ISO 9001 · CERTIFIED**
**ISO 14001 · CERTIFIED**
**OHSAS 18001 · CERTIFIED**
**EN 12201 · CERTIFIED**
**TURKISH LLOYD · ON REQUEST**
